

# Baolifeng (BLF) Tools Co., LTD

www.blf-tools.com

## CO EP series

### hydraulic split-unit crimping tools

- It is applicable to professional use of projects inside and outside distribution house, various connection metals and overhead under the cable
- 10kv-500kv high pressure cable bushing, wire clip, naked terminal, hexagonal pressing can ensure tightness and non-easy shedding, with good electric conduction
- It can be combined with electric pumps of DYB-63A, CP-700 series, engine motor



Model: **CO-630A**

- Crimping range (mm<sup>2</sup>) -AL Terminal: 120-500
- Crimping range (mm<sup>2</sup>) -CU Terminal: 150-630
- Crimping force: 35
- Stroke (mm): 26
- Weight (kg): 17.5
- Standard dies (mm<sup>2</sup>): 150, 185, 240, 300, 400, 500, 630
- Packing & Size (mm): 380\*295\*145
- Type: Hexagon



Model: **ZY0-400**

- Crimping range (mm<sup>2</sup>) -AL Terminal: 120-500
- Crimping range (mm<sup>2</sup>) -CU Terminal: 150-630
- Crimping force: 30
- Stroke (mm): 24
- Weight (kg): 11.5
- Standard dies (mm<sup>2</sup>): 150, 185, 240, 300, 400, 500, 630
- Packing & Size (mm): 385\*295\*145
- Type: Hexagon



Model: **FM-400**

- Crimping range (mm<sup>2</sup>) -AL Terminal: 35-300
- Crimping range (mm<sup>2</sup>) -CU Terminal: 50-400
- Crimping force: 16
- Stroke (mm): 20
- Weight (kg): 9
- Standard dies (mm<sup>2</sup>): 50, 70, 95, 120, 150, 185, 240, 300, 400
- Packing & Size (mm): 355\*90\*195
- Type: Hexagon

## CO EP series

## split-unit crimping tools

- It is applicable to professional use of projects inside and outside distribution house, various connection metals and overhead under the cable
- 10kv-500kv high pressure cable bushing, wire clip, naked terminal, hexagonal pressing can ensure tightness and non-easy shedding, with good electric conduction
- It can be combined with electric pumps of DYB-63A, CP-700 series, engine motor



Model: **CO-1000**

- Crimping range (mm<sup>2</sup>)-AL Terminal: 300-800
- Crimping range (mm<sup>2</sup>)-CU Terminal: 400-1000
- Crimping force: 55
- Stroke (mm): 24
- Weight (kg): 32
- Standard dies (mm<sup>2</sup>): 400, 500, 630, 800, 1000
- Packing & Size (mm): 445\*295\*145

• Type: Hexagon



Model: **EP-510H**

- Crimping range (mm<sup>2</sup>)-AL Terminal: 10-300
- Crimping range (mm<sup>2</sup>)-CU Terminal: 16-400
- Crimping force: 13
- Stroke (mm): 38
- Weight (kg): 5.6
- Standard dies (mm<sup>2</sup>): 50, 70, 95, 120, 150, 185, 240, 300, 400
- Packing & Size (mm): 355\*90\*195

• Type: Hexagon



Model: **EP-410H**

- Crimping range (mm<sup>2</sup>)-AL Terminal: 10-240
- Crimping range (mm<sup>2</sup>)-CU Terminal: 16-300
- Crimping force: 12
- Stroke (mm): 30
- Weight (kg): 4.8
- Standard dies (mm<sup>2</sup>): 50, 70, 95, 120, 150, 185, 240, 300
- Packing & Size (mm): 355\*90\*195

• Type: Hexagon



Model: **CYO-400B**

- Crimping range (mm<sup>2</sup>)-AL Terminal:10-300
- Crimping range (mm<sup>2</sup>)-CU Terminal:16-400
- Crimping force:12
- Stroke (mm):32
- Weight (kg):5
- Standard dies(mm<sup>2</sup>):50,70,95,120,150,185,240,300,400
- Packing&Size (mm):355\*90\*195
- Type: Hexagon



Model: **CO-200S**

- Crimping force:100
- Weight (kg):33
- Piston travel (mm):24
- Size (mm):374\*140
- Brass Alu casing pipe: steel Alu casing pipe 76/steel casing pipe 36
- Remark: Two-circuit electrically driven pump



Model: **CO-100S**

- Crimping force:200
- Weight (kg):97
- Piston travel (mm):35
- Size (mm):472\*250
- Brass Alu casing pipe: steel Alu casing pipe 90/steel casing pipe 50
- Remark: Two-circuit electrically driven pump